

# EL03/EL302A Digital Level



- **■** Far measuring range:≤110m
- Accuracy: EL03 $\leq$   $\pm$ 0.3mm, EL302A $\leq$   $\pm$ 0.7mm
- Reliable reading, even in dim light conditions
- Remote control measurement by bluetooth(EL03)
- Onboard programs, such as BF, BFFB, BFBF, BBFF, FBBF, stake out, intermediate
- LCD display presents all important measured data at a glance and shows the next step to take
- Quicker and easier than an optical level; Easy one-touch operation, simply push the MEAS button
- Quick height and distance result the reading is displayed almost instantly with measurement

## EL03/EL302A Digital Level

#### Features

- LCD display, with illumination
- Alphanumeric keyboard, 24 keys
- Automatic height and delta height calculation
- Optical reading is available
- Internal memory(3000 points) or SD card for data storage, supports USB, RS-232C ports and Bluetooth(EL03) for data transfer

#### Technical data

	EL03	EL302A	
Accuracy			
Standard deviation of 1km double r	run(ISO 17123-2)		
Electronic measurement	$\pm$ 0.3mm*	±0.7mm*	
Optical measurement	$\pm 1.5$ mm*	±1.5mm*	
Electronic measurement			
Time for single measurement	≤.	≤2s	
Range	2-110m	2-105m	
Measurement modes	Single, avera	Single, average, tracking	
Display resolution(m/inch selectab	le for EL03/EL302A )		
Height	0.01mm	0.01mm/0.00001ft	
Distance	1mm/(	1mm/0.001ft	
Telescope			
Clear objective aperture	451	45mm	
Magnification	30	30×	
Field of view at 100m	2.6	2.6m	
Shortest focus distance	1.0	1.0m	
Automatic compensator			
Working range	1-	14′	
Setting accuracy	±0.3"	±0.5"	
Power			
Battery	2000mAh Ni-MF	2000mAh Ni-MH rechargeable	
Continuous operation time	12 hours	12 hours(At+12℃)	
Measurement programs			
On-board programs	BF, BFFB, BFBF, BBFF, FBBF, Sta	BF, BFFB, BFBF, BBFF, FBBF, Stake out, intermediate	
Onboard adjustment	,	YES	
Others			
Memory		3000 points, support SD card	
Display		LCD, 7linesX32characters	
Keyboard		Alphanumerical key board	
Interface		USB, RS-232C optional, Bluetooth(Only for EL03)	
Sensitivity of circular level		8' /2mm	
Water and dust protection		IP54	
Operating Temp		-20°C~ +50°C	
Net Weight	3	3kg	

<sup>\*</sup> Depending on staff and levelling technique.

Illustrations, descriptions and technical specifications are not binding and may change



### Suzhou FOIF Co.,Ltd.

TEL:+86 512 65224904 FAX:+86 512 65230619 Http://www.foif.com

E-mail:internationalsales@foif.com.cn

ADD: 18 Tong Yuan Road, Suzhou 215006, P.R. China



